



Tsunami® QuickBridge 8100 Series

End-to-End Broadband Wireless Product Portfolio

Proxim Wireless offers extremely reliable, secure and easily-deployed solutions for interconnecting corporate and telecommunications networks. This portfolio includes:

- **Gigalink®** – Carrier-class alternative to fiber, up to 1.25Gbps
- **Lynx.GX®** – Cellular voice and data backhaul, up to DS3 interface
- **Tsunami®.GX®** - Carrier-class IP Ethernet Bridge for voice and data backhaul for service providers and enterprise applications
- **QuickBridge®** – Easiest-to-install “Hop-in a- box” complete kit Ethernet Bridge for campus and small business networks

Proxim Wireless is a global pioneer of end-to-end broadband wireless systems that deliver the quadruple play. From Wi-Fi to wireless Gigabit Ethernet – our WLAN, Mesh, WiMAX and point-to-point products are available through our extensive global channel networks.

Presenting a Wireless Backhaul Solution that Exceeds 4G Speed Requirements with 300Mbps Bandwidth!

With over 20 years in wireless innovation, Proxim introduces the Tsunami® QB-8100, an incredibly cost-effective, high performance and non-line-of-sight 4G point-to-point (PtP) wireless backhaul solution. With 300Mbps data rates in a complete “Hop-in-a-Box” solution, deployments in networks of all sizes will enjoy a quick return on investment.

With incredible channel capacity & flexibility, excellent spectrum efficiency and a highly evolved prioritization platform tailored to deliver voice, video and data applications, the Tsunami® QB-8100 satisfies carriers, wireless service providers and Government organizations with requirements for fast and reliable 4G wireless backhaul.

Leveraging the advantages of OFDM and the latest MIMO radio innovations, the Tsunami® QB-8100 draws on Proxim’s proprietary Wireless Outdoor Router Protocol (WORP) to deliver wireless performance in excess of 4G products on the markets today.

World-class Performance

- A Point-to-Point system that delivers a 300 Mbps data rate link at distances of over 5 miles (8 km)
- Very low latency of the order of 2 to 3 ms to support voice and video applications over long distances
- Built-in feature rich network protocols for bridging, routing and gateway functionality

Non-Line-of-Sight and Advanced Features

- Non-line-of-sight capable, utilizing OFDM and enhanced MIMO techniques to penetrate through obstructions better
- Features dual Gigabit Ethernet ports with PoE out to power other devices like surveillance cameras and additional radios
- Enables packet identification to create unique and sophisticated service rules and tiered service classes with ease

Widest Range of Frequencies

- Provides flexible channel planning with support for 4.9 - 6.0 GHz and 2.3 - 2.5 GHz frequencies
- Operates in licensed and unlicensed frequency spectrums and comes as a complete “Hop-In-A-Box” with a set of accessories for even greater ease of installation

Carrier-Grade Security

- Implements tiered security layers for the most secure outdoor wireless communications in the unlicensed frequency spectrum
- Utilizes Proxim’s Wireless Outdoor Routing Protocol (WORP), which prevents snooping, and features highly-secure remote management via SSL, SSH and SNMPv3
- Provides advanced AES encryption for military-grade over-the-air communications and radio mutual authentication eliminates unauthorized use of the system by rogue subscriber units and man-in-the-middle attacks

Cost Effective and Ease of Use for Quick Return on Investment

- Complete “Hop-In-A-Box” compact outdoor form factor allows unprecedented ease of installation
- Suitable for the carriers, WISP and Government markets
- Certified for deployments in the Americas, Europe and Asia
- The most cost-effective, high performance point-to-point solution from Proxim, enabling any deployment to enjoy a quick return on investment

Tsunami® QuickBridge 8100 Series

Technical Specifications

PRODUCT MODELS					
QB-8100-LNK	Tsunami QB 8100 Link, 300 Mbps, MIMO 3x3, Type-N Connectors (Two QB-8100-EPA)				
QB-8150-LNK	Tsunami QB 8150 Link, 300 Mbps, MIMO 2x2, 23 dBi panel antenna (Two QB-8150-EPR)				
INTERFACES					
WIRED ETHERNET	Two auto MDI-X RJ45 10/100/1000Mbps Ethernet - Port #1 with PoE in & Data - Port #2 with PoE out (802.3af pin out) & Data				
WIRELESS PROTOCOL	WORP (Wireless Outdoor Router Protocol)				
RADIO & TX SPECS					
MIMO	3x3 MIMO				
MODULATION	OFDM				
FREQUENCY	2.3 – 2.5 GHz 4.9 – 6.0 GHz (Subject to Country Regulations)				
CHANNEL SIZE	40 MHz, 20 MHz, 10 MHz, 5 MHz channel bandwidths				
DATA RATE	MCS 0 to 15 for High Throughput mode (6.5 – 300 Mbps) with Dynamic Data Rate Selection				
TX POWER	Up to 21dBm (two Tx chain)				
TX POWER CONTROL	0 – 25 dB, in 0.5 dB steps. Automatic TPC with configurable EIRP limit				
RX SENSITIVITY (BER=10 ⁻⁶)	Channel Size	40 MHz	20 MHz	10 MHz	5 MHz
	MCS 0	-87 dBm	-93 dBm	-94 dBm	-96 dBm
	MCS 7	-71 dBm	-75 dBm	-78 dBm	-81 dBm
	MCS 8	-87 dBm	-93 dBm	-94 dBm	-95 dBm
	MCS 15	-69 dBm	-71 dBm	-74 dBm	-77 dBm
LATENCY	< 3 msec				
ANTENNA	Model QB-8100-EPA includes three N-Type Antenna Connectors with built in Surge Protection Model QB-8150-EPR includes an Integrated 2x2 MIMO 23dBi Dual Polarized Antenna				
MANAGEMENT					
LOCAL	RS-232 serial (RJ11 to DB-9 dongle provided)				
REMOTE	Telnet and SSH, Web GUI and SSL, TFTP, SNMPv3				
SNMP	SNMP v1-v2c-v3, RFC-1213, RFC-1215, RFC-2790, RFC-2571, RFC-3412, RFC-3414, Private MIB				
OTHER	Syslog, sFlow™ agent, SNTP and local time				
SECURITY					
ENCRYPTION	AES-CCM 128 bits				
AUTHENTICATION	Internal MAC Address Control List, Radius based Authentication				
NETWORK					
MODES	Bridging(support LACP through external switches), Routing (RIP v2 and IP tunneling)				
GATEWAY FEATURES	DHCP Server & relay, NAT with Std ALGs				
QoS	Asymmetric Bandwidth Control	Uplink and Downlink CIR Control "committed information rate" per service flow Uplink and Downlink MIR Control "maximum information rate" per service flow			
	Packet Classification Capabilities	802.1D/802.1Q/802.1p priority, IPTOS, VLAN ID, IP source/destination address, source/destination port, Ethernet source/destination address, IP protocol, and Ethertype			
	Scheduling	Best Effort, Real Time Polling Services			
VLAN	802.1Q: Management VLAN. Transparent, Access, Trunk and Mixed mode. QinQ double tagging				
ENVIRONMENTAL SPECS					
TEMPERATURE					
OPERATING	-40° to 60°C (-40° to 140° Fahrenheit)				
STORAGE	-55° to 80°C (-67° to 176° Fahrenheit)				
HUMIDITY	Max 100% relative humidity (non-condensing)				
IP RATING	IP67				
WIND LOADING	125 mph				
PHYSICAL SPECS					
DIMENSIONS					
PACKAGED	Model QB-8100-EPA: 14.56 x 13.69 x 8.18 in. (370 x 348 x 208 mm) Model QB-8150-EPR: 15.94 x 15.94 x 9.21 in. (405 x 405 x 234 mm)				
UNPACKAGED	Model QB-8100-EPA: 10.5 x 10.5 x 3.38 in (267 x 267 x 86 mm) Model QB-8150-EPR: 14.17 x 14.17 x 3.70 in (370 x 370 x 94 mm)				
WEIGHT					
PACKAGED	Model QB-8100-EPA: 15 lbs (6.8 kg) Model QB-8150-EPR: 16.31 lbs (7.4 kg)				
UNPACKAGED	Model QB-8100-EPA: 7.7 lbs (3.5 kg) Model QB-8150-EPR: 9.0 lbs (4.1 kg)				
SAFETY STANDARDS	UL 60950, CAN/CSA-C22.2 No. 60950, IEC 60950, EN 60950				
PACKAGE CONTENTS	<ul style="list-style-type: none"> ■ One Tsunami® QB-8100-LNK based on two QB-8100-EPA with three N-type surge protected connectors or One Tsunami® QB-8150-LNK based on two QB-8150-EPR with an integrated 23dBi dual polarized panel antenna ■ Two power injector and country specific power cord ■ Two Wall / Pole mounting kit ■ Two Connector weatherproofing kit (Includes all recommended weatherproofing material) ■ Two Serial (RJ-11 to DB9) dongle ■ Two Grounding kit ■ Two Gigabit PoE Surge Arrestor ■ One Quick Installation Guide 				
MTBF & WARRANTY	80,000 hours & 1-year on parts and labor; ServPak Extended Support available.				

APPLICATIONS

• Backhaul to a Central POP

Avoid expensive installation and recurring charge of a second wire line backhaul to a remote virtual POP

• Leased Line Redundancy

Eliminate recurring DS-3 leased line charges with one time installation charge of a QuickBridge link

• Repeater

Extend distance or overcome path blockage by adding point-to-point hops

• High-bandwidth Last Mile Access

Use QuickBridge to deliver TLS (Transparent LAN Services) to corporate parks

• Inter-POP Redundancy

Avoid downtimes caused by a wireline backhaul failure by adding a QuickBridge link as an inter-POP redundancy

For detailed technical specifications, please go to <http://proxim.com/products/ptpwireless-backhaul/tsunamiir-qb-8100-series/tsunamiir-qb-8100>

©2011 Proxim Wireless Corporation. All rights reserved. Proxim is a registered trademark and the Proxim logo and Tsunami® are trademarks of Proxim Wireless Corporation. All other trademarks mentioned herein are property of their respective owners. Specifications are subject to change without notice.
DS_1211_QB8100_US



Proxim Wireless Corporation
www.proxim.com