

## TreuVaz 5025 Series ODU

Point-to-Point Radio

TV-5025-SE



### Product Description

TV-5025-SE is a carrier-class radio that belongs to the TreuVaz 5025 Series and supports 4.9 to 5.9 GHz frequency range.

The Radio complies with Universal, FCC/IC, MII & WPC regulations with a factory default of 5.8 GHz FCC/IC.

TV-5025-SE delivers up to 25 Mbps throughput and up to 4xE1s/T1s over an extended range.

The radio is connectorized for external antenna (2 x N-type).

### Product Highlights

- 25 Mbps Ethernet net throughput and 4xE1s/T1s Native TDM interfaces
- Long range - Up to 120 km / 75 miles
- Telco-grade, extremely robust in harsh conditions
- Supports intra-site and inter-site synchronization to maximize capacity
- Adaptive asymmetric throughput – dynamic allocation between uplink and downlink
- Advanced OFDM & MIMO technologies for operation in nLOS/NLOS and dense radio environments



Loyalty Connection

## Product Specifications:

Configuration					
Architecture	Outdoor Unit connectorized for external antenna (2 x N-type)				
PoE to ODU Interface	Outdoor CAT-5e; Maximum cable length: 100m for 10/100BaseT				
Radio					
Max Capacity	25 Mbps net aggregate throughput (up to 4xE1s/T1s plus Ethernet)				
Range	Up to 120 km / 75 miles				
Channel Bandwidth	Configurable: 5, 10, 20 MHz (for the default band)				
Modulation	2x2 MIMO-OFDM (BPSK/QPSK/16QAM/64QAM)				
Adaptive Modulation & Coding	Supported				
Automatic Channel Selection	Supported				
DFS	Supported (FCC/IC)				
Diversity	Supported				
Spectrum Viewer	Supported				
Max Tx Power	25 dBm				
Duplex Technology	TDD				
Error Correction	FEC k = 1/2, 2/3, 3/4, 5/6				
Encryption	AES 128; FIPS 197				
Support Indoor units	IDUs: TreuRack (RackMount IDU) , TreuDop (DeskTop IDU) , TreuPoz PoE Devices (TP-POE-AC-GBE-X)				
Uplink / Downlink Allocation	Configurable: Symmetric or Asymmetric				
QoS	Packet classification to 4 priority queues according to 802.1P or Diffserv				
VLAN Support	802.1Q, QinQ, 4094 VLANs				
Ethernet Ring Protection	Supported, including Ethernet 1+1				
TDD Intra Site Synchronization	Supported				
TDD Inter Site Synchronization	Supported				
Monitored Hot Standby	1+1 with TreuNetz Point-to-Point Radio				
Supported Bands					
Band	Channel BW 5MHz [GHz]	Channel BW 10MHz [GHz]	Channel BW 20MHz [GHz]	Channel BW 40MHz [GHz]	Radio Compliance
4.9 GHz Universal	4.8975-5.0025	4.895-5.005	4.890-5.010	-	Universal
5.1 GHz Universal	5.1475-5.3375	5.145-5.340	5.140-5.345	-	Universal
5.4 GHz Universal	5.4725-5.7225	5.470-5.725	5.465-5.730	-	Universal
5.8 GHz FCC/IC (default)	5.7275-5.8475	5.725-5.850	5.725-5.850	-	FCC 47CFR Part 15.247; IC RSS-210
5.8 GHz MII	5.7375-5.8375	5.735-5.840	5.730-5.845	-	CMIIT RTA
5.9 GHz Universal	5.7275-5.9525	5.725-5.955	5.720-5.960	-	Universal
5.8 GHz WPC	5.8325-5.8675	5.830-5.870	5.825-5.875	-	WPC (India) G.S.R 38(E) dated 19 January, 2007 Notification
4.9 GHz FCC/IC	4.9425-4.9875	4.940-4.990	4.940-4.990	-	FCC 47CFR Part 90 Subpart Y; IC RSS-111
5.2 GHz FCC/IC	5.2525-5.3475	5.255-5.345	5.255-5.345	-	FCC 47CFR Part 15.407; IC RSS-210
5.4 GHz FCC/IC	5.4775-5.7175	5.480-5.715	5.480-5.715	-	FCC 47CFR Part 15.407; IC RSS-210
5.1 GHz FCC/IC	5.1575-5.2475	5.160-5.245	5.160-5.245	-	FCC 47CFR Part 15.407; IC RSS-210
ODU Dimensions	21(w) x 17(h) x 7(d) cm				
ODU Weight	1.2 kg / 2.65 lbs				
Power Feeding	Power provided over ODU-IDU cable				
Power Consumption	<12W				
Operating Temperatures	-35°C to 60°C / -31°F to 140°F				
Humidity	100% condensing, IP67 (totally protected against dust and against immersion up to 1m)				
FCC/IC (cTUVus)	UL 60950-1, UL 60950-22, CAN/CSA C22.2 60950-1, CAN/CSA C22.2 60950-22				
ETSI	EN/IEC 60950-1, EN/IEC 60950-22				
FCC	47 CFR Class B, Part15, Subpart B				
ETSI	EN 300 386, EN 301 489-1, EN 301 489-4				
CAN/CSA-CEI/IEC	CISPR 22-04 Class B				

### Ordering Info

Part Number: TV-5025-SE

Description: TreuNetz - TreuVaz 5025 Series ODU , connectorized for external antenna (2 x N-type), supporting multi frequency bands at 5.x GHz, factory default 5.8 GHz FCC/IC.



www.spreadco.ir  
info@spreadco.ir  
Tel:88754017

The Treunetz name is a registered trademark of Cynergics Technologies GmbH © All rights reserved, October, 2015

info@treunetz.at  
www.treunetz.at  
Wien-Austria